

QUESTIONS & ANSWERS

Kill your exam at first Attempt



SUN

310-620

EDS Certified Sun Enterprise 10K Server Administrator

- C. format
- D. reconfig

Answer: D

QUESTION: 58

What must be completed before DR detaching an I/O board?

- A. Power off the board
- B. Stop all signals to that board
- C. Deconfigure all I/O on the board
- D. Reboot the domain

Answer: B

QUESTION: 59

Which file does init_attach update?

- A. domain_config
- B. domain_history
- C. eeprom.<domain name>
- D. obp

Answer: A

QUESTION: 60

When using DR, what is the minimum number of system boards allowed in a domain?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: A

QUESTION: 61

Once a system board has been drained, what command is used before quitting the DR operation?

- A. dr_stop
- B. abort_detach
- C. exit
- D. abort_dr

Answer: B

QUESTION: 62

What command is used to cause the fans to provide extra airflow to the platform?

- A. fan -a fast
- B. fan -s fast
- C. fan -p fast
- D. fan -x faster

Answer: B

QUESTION: 63

When viewing the control boards through hostview, the icons display which symbols?

- A. B T
- B. J C
- C. Firmware level
- D. Network address

Answer: B

QUESTION: 64

Which hostinfo command provides fan status information?

- A. hostinfo -f
- B. hostinfo fans
- C. hostinfo -F
- D. hostinfo -ft

Answer: C

QUESTION: 65

What command is used to display the power status on each system board?

- A. power
- B. power -a sb
- C. show_power
- D. show_power -r sb

Answer: A

For More exams visit <https://killexams.com> -



Kill your exam at First Attempt....Guaranteed!