

# QUESTIONS & ANSWERS

Kill your exam at first Attempt



**HP**

# HP0-Y22

*Implementing HP ProCurve MultiService*

**QUESTION: 58**

To enable L3 Mobility on a VSC, which parameter on the VSC must be disabled?

- A. Access Control
- B. Authentication
- C. VLANs
- D. Wireless security filters

**Answer: A**

**QUESTION: 59**

Which feature would you enable to enhance Layer 2(L2) Roaming?

- A. rapid authentication
- B. seamless roaming
- C. single network AP hopping
- D. WPA2 Opportunistic Key Caching

**Answer: D**

**QUESTION: 60**

In a controlled mode network, when is the MSM Access Point egress VLAN configured?

- A. during the discovery process
- B. during the VSC to Group binding process
- C. during the network VLAN creation process
- D. during the Virtual Service Community creation process

**Answer: B**

**QUESTION: 61**

When configuring the MSM Controller for a Controlled mode network, at what point is the AP's VSC egress VLAN configured?

- A. when the Group is created
- B. when the AP is synchronized with its Group
- C. when the specified VLAN is created
- D. when the VSC is bound to the Group

**Answer:** D

**QUESTION:** 62

A wired client is sending its incoming traffic to the VLAN port on an MSM Controller. In a WLAN configured with VSCs 1-4, which VSC will be selected to pass the traffic from the wired client?

- A. Default VSC
- B. VSC 2
- C. VSC 3
- D. VSC 4

**Answer:** A

**QUESTION:** 63

On a VSC, which options can be specified for egress VLANs?(select three)

- A. Authenticated traffic
- B. Default gateway traffic
- C. IP filtered traffic
- D. Intercepted traffic
- E. Unauthenticated traffic
- F. Untagged traffic

**Answer:** A, D, E

KILLEXAMS.COM

For More exams visit <https://killexams.com> -



*Kill your exam at First Attempt....Guaranteed!*